


EPIC-QM57

EPIC Express Board with Intel® Core™ i7/ i5/ Celeron® (32nm) Processor



Features

- Intel® Core™ i7/ i5/ Celeron® (32nm) Processor
- Intel® QM57
- SODIMM DDR3 800/1066 Memory, Max. 4 GB, 8 GB (Optional)
- Gigabit Ethernet x 2
- Up to 18/24-bit Dual-channel LVDS LCD, CRT, DVI, DisplayPort™ (Optional)
- 2CH HD Audio
- SATA 3.0Gb/s x 2, Type 2 CompactFlash™
- USB2.0 x 6, COM x 4, 8-bit Digital I/O
- PCI/104-Express (PCI-104 + PCIe/104)
- Expansion: Mini Card x 1
- Supports iAMT6.0, RAID 0 & 1 (Optional)
- +12V Only Operation

Specifications

System	
Form Factor	EPIC Express Board
Processor	Intel® Core™ i7/ i5/ Celeron® (32nm) (Socket-988)
System Memory	204-pin SODIMM DDR3 800/1066 Memory, Max. 8 G
Chipset	Intel® QM57
I/O Chipset	ITE8781
Ethernet	10/1000/1000Base-TX x 2 (Intel® 82577LM and Intel® 82574L respectively), RJ-45 x 2
BIOS	AMI Plug & Play BIOS – 8 MB Flash
Wake On LAN	Yes
Watchdog Timer	Generates a time-out system reset
H/W Status Monitoring	Supports Power Supply Voltage, Fan Speed and Temperature Monitoring
Expansion Interface	PCI-104, PCIe/104 connector, Mini Card
Battery	Lithium battery
Power Requirement	+12V
Power Consumption (Typical)	Intel® i7-620M, DDR3 1066MHz, 1 GB 4.02A@+12V
Board Size	4.5" x 6.5" (115mm x 165mm)
Gross Weight	1.2 lb (0.5 Kg)
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)
Storage Temperature	-40°F ~ 176°F (-40°C ~ 80°C)
Operating Humidity	0% ~ 90% relative humidity, non-condensing
MTBF (Hours)	70,000
Display	
	Supports CRT/ LCD/ DVI simultaneous/ dual view display
Chipset	Intel® CPU integrated
Memory	Shared system memory up to 512 MB
Resolutions	Up to 1920 x 1440@colors for CRT Up to 1920 x 1200 for DVI/LCD
LCD Interface	18/24-bit dual-channel LVDS
I/O	
Storage	SATA 3.0Gb/s x 2 (RAID 0,1 optional), Type 2 CompactFlash™ x 1
Serial Port	RS-232 x 3, RS-232/422/485 x 1
Parallel	SPP/EPP/ECP Mode
USB	USB2.0 x 6
PS/2 Port	Keyboard x 1, Mouse x 1
Digital I/O	Supports 8-bit (Programmable)
Audio	Line-in/ Line-out/ CD-in & MIC-in
Touch Screen (Optional)	Supports 4/5/8-wire resistive touch screen




Packing List

- Cooler
- Product CD
- EPIC-QM57

EPIC-QM57

Dimension

Unit: mm



Ordering Information

Part Number	CPU	Fan/Fanless	Display	LVDS	Storage	LAN	USB	RS-232	RS-232/422/485	Expansion Slot	Power	Temp
TF-EPIC-QM57-A11	Socket-988	FAN	DVI+LVDS	24b, 2CH	SATA x 2 CompactFlash™ x 1	GbE x 2	6	3	1	PCI/104-Express x 1 Mini Card x 1	DC12V	0°C ~ 60°C

Optional Accessories

- **1700290150**
DVI-I to DVI + VGA Cable, Length 15cm
- **1700060157**
KB/Mouse Cable
- **TF-PER-C41C-A10**
4 COM Ports Mini Card